

# Tau 330 RSC

## Boosts Your Business

### Technical Specifications

---

**Printing technology:**

Single-pass UV inkjet technology (drop on demand + variable drop size) with Dimatix Samba G3L printing heads.

---

**Printing quality:**

Print resolution: 1,200 x 1,200 dpi; drop size = 2 pl

Visual resolution: 2,400 x 2,400 dpi

---

**Printing speed:**

High-speed print mode: 78 lin. m/min, (255 lin. ft./min)

White under print mode: 52 lin. m/min, (170 lin. ft./min)

---

**Print width:**

Tau 330: max. 330 mm (13 in.)

---

**Ink/colors:**

High-performance UV inkjet inks

Colors: CMYK; optional: orange, violet and green, optional: white.

---

**Substrate specification:**

Width: 165 – 350 mm (6.5 – 13.7 in.); thickness: >20 – 500 microns

---

**Substrate type:**

Coated and uncoated, supported and unsupported substrates

Paper, white and transparent film, PP, PE, PVC, PET, BOPP, aluminum foil

---

**Material transport:**

Roll diameter: max. 680 mm (26.5 in.) – max. 120 kg (264 lb)

Roll diameter with jumbo unwinder/rewinder: max. 1,000 mm (39,37 in.) – max. 240 kg (529 lb)

---

**UV curing:**

Optional chill roller; optional inert gas chamber for low ink odor

---

**Optional:**

Corona treatment, web cleaning, insetter 100%, video inspection, variable data printing

---